

ESCOMATIC D6R

Kind : Single-spindle lathe
Brand : ESCOMATIC
Model : D6R
Serial Nr: 2419
Stock Nr : 9105



TECHNICAL DETAILS

| | |
|---|--|
| - Revolver tool number | : 4 |
| - Max. spindles drilling, tapping, threading | : 32 [mm] |
| - Max. spindle counter-collet | : 36 [mm] |
| - Max. tapping / threading diameter | |
| steel | : 4 [mm] |
| brass | : 5 [mm] |
| - Max. tapping / threading length | : 25 [mm] |
| - Max. drilling spindles clamping diameter | : 6 [mm] |
| - Max. counter-collet clamping diameter | : 6.35 [mm] |
| - Drilling spindle rotation speeds | : 25, 40, 65, 100, and 150 x 100 [Rpm] |
| - Tapping / threading spindle speeds | : 6, 9, 13, 20 and 30 x 100 [Rpm] |
| - Changing time revolver head position (1/4 turn) | : 1/4 [sec] |
| - Levers report | |
| drilling | : 1/1 |
| counter-collet in revolver head | : 1/1 |
| self tapping screw thread (director thread) | : 1/3 |
| - Main motor | |
| power | : 2.2 [kW] |
| normal speed | : 2820 [Rpm] |
| - Normal motor tapping / threading | |
| power | : 0.45 [kW] |
| normal speed | : 1380 [Rpm] |
| - Floor space | |
| without brushholder | : 900 x 1800 [mm] |

Kind : Single-spindle lathe

Brand : ESCOMATIC

Model : D6R

Serial Nr: 2419

Stock Nr : 9105

with brushholder : 900 x 3400 [mm]

- Weight (without packing) : 1090 [kg]